


## TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

<b>ONE STEP</b> POLISHING COMPOUND	
<b>Art. No.</b>	
11249 (250 g) 11024 (1 kg) 11386 (100 g x 12/display)	
<b>COLOUR:</b> white	
<b>DENSITY:</b> 1,09 g/cm <sup>3</sup>	

### PRODUCT DESCRIPTION

**BRAYT ONE STEP** is a polishing compound suitable to use on every kind of varnish used in automotive sector, including hard scratch resistant lacquers (also ceramic lacquers). Product recommended for fresh and old paint coatings. Easily removes scratches and traces after P2000 sanding paper. Can be used with most of the applicators available on the market (polishing sponge, wool, microfiber pad). Silicone free, no filler.

- Cut level: 6/10
- Gloss level: 9/10
- Processing: manual work, mechanical work (rotary machine; orbital machine)

### RECOMMENDED APPLICATORS

- BRAYT POLISHING FOAM HARD yellow
- BRAYT POLISHING FOAM SOFT grey
- BRAYT LAMBSWOOL „D” yellow
- BRAYT LAMBSWOOL „MM” white
- BRAYT ORANGE PEEL REMOVAL PAD „JEANS”
- BRAYT ORANGE PEEL REMOVAL PAD „CORDUROY”

### USAGE

- On hard and scratch-resistant lacquers, use the compound with a lambswool or hard polishing foam.
- Apply a small amount of polishing compound on the surface to be polished.
- When using a new polishing pad, it is recommended to apply the compound on the applicator and pre-polish the surface.
- Polish in a speed range of 800 – 1600 RPM, applying light or medium pressure, depending on the surface.
- Polish surfaces until the scratches have been removed.
- Remove all polishing compound residue using microfiber cloth.
- Change applicator to a soft sponge and polish to reach perfect gloss.
- When polishing large surfaces, it is recommended to polish smaller sections at a time.

### STORAGE

Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children.

### EXPIRY DATE

ONE STEP	24 months from production date.
----------	---------------------------------

**LIMITATION OF LIABILITY**

The information contained in this TDS sheet is up-to-date and correct on the day the information is released

Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's

knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship. .

TROTON Sp. z o.o.  
Ząbrowo, Poland.