

**SAFETY DATA SHEET**

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01



**Techpol Limited** Unit 4 Rushy Platt, Wootton Bassett Road, Swindon, Wiltshire SN5 8WQ  
Phone: 01793 871550 [www.techpol.com](http://www.techpol.com)

## 1. Identification of the substance/preparation and of the company/undertaking

**Product name** 10747 2K Clearcoat

**Product code** 10747

**Intended use of the substance/preparation**

Coating for professional use

**Company/Undertaking Identification**

Techpol Ltd

Unit 4, Rushy Platt, Wootton Bassett Road, Swindon SN5 8WQ

Telephone +44 (0) 1793 871550

**Information on SDS**

Responsible Department Regulatory Affairs

Telephone +44 (0)1793 871550

E-mail address enquiries@techpolltd.com

**Emergency Information**

Emergency telephone +44 (0)1793 871550

## 2. Hazards identification

The preparation is classified as dangerous in accordance with Directive 1999/45/EC.

**Human health hazards**

Classification : Harmful; dangerous for the environment; Flammable;

Flammable. Harmful by inhalation and in contact with skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Special hazard instructions for humans and environment**

Contains epoxy constituents. See information supplied by the manufacturer. Contains: phthalic anhydride; neodecanoic acid, 2,3-epoxypropyl ester. May produce an allergic reaction.

## 3. Composition/information on ingredients

**Chemical characterization**

Mixture of synthetic resins and solvents

**Hazardous components**

Substances presenting a health or environmental hazard within the meaning of the DSD 67/548/EEC referring to 1272/ 2008 annex VI

EC-No.	CAS-No.	Chemical Name	Concentration	Classification
215-535-7	1330-20-7	xylene	15.00 - < 20.00 % R10	Xn; R20/21 Xi; R38
204-658-1	123-86-4	n-butyl acetate	12.50 - < 15.00 % R10	R66 R67
203-933-3	112-07-2	2-butoxyethyl acetate	5.00 - < 7.00 % Xn; R20/21	

Copies may be made only for those using Techpol Ltd products.

EC-No.	CAS-No.	Chemical Name	Concentration	Classification
202-849-4	100-41-4	ethylbenzene	3.00 - < 5.00 % F; R11	Xn; R20



Company Registration No: 4597527

VAT Registration No: 797 8388 38

**SAFETY DATA SHEET**

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

265-199-0 64742-95-6	solvent naphtha (petroleum), light aroma ( $<0,1\%$ benzene)	1.00 - $< 2.00 \%$	R10	Xi; R37 N; R51/53 Xn; R65 R66 R67 NotaH NotaP
202-436-9 95-63-6	1,2,4-trimethylbenzene	0.50 - $< 1.00 \%$	R10	Xn; R20 Xi; R36/37/38 N; R51/53
201-607-5 85-44-9	phthalic anhydride	0.25 - $< 0.50 \%$	R42/43	Xi; R41 Xi; R37/38 Xn; R22
203-604-4 108-67-8	mesitylene	0.20 - $< 0.25 \%$	R10	Xi; R37 N; R51/53
247-979-2 26761-45-5	neodecanoic acid, 2,3-epoxypropyl ester	0.20 - $< 0.25 \%$	N; R51/53	R43
203-132-9 103-65-1	n-propylbenzene	0.10 - $< 0.20 \%$	R10	Xn; R65 Xi; R37 N; R51/53

Up to the given revision date of this safety data sheet no REACH registration numbers are assigned to the chemical substances used in this preparation.

**Additional advice**

See full text of R-phrases in chapter 16.

**4. First aid measures****General advice**

When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

**Inhalation**

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

**Skin contact**

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

**Ingestion**

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

Copies may be made only for those using Techpol Ltd products.

**5. Fire-fighting measures****Hazardous combustion products**

Fire will produce dense black smoke containing hazardous combustion products (see heading 10). Exposure to decomposition products may be a hazard to health.

**Fire and Explosion Hazards**

Flammable liquid. Vapours may form explosive mixtures with air. Remove all sources of ignition.

**Suitable extinguishing media**

Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical, Water spray.



Company Registration No: 4597527

VAT Registration No: 797 8388 38

**Extinguishing media which shall not be used for safety reasons**

High volume water jet

**Special Protective Equipment and Fire Fighting Procedures**

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

**Additional advice**

Cool closed containers exposed to fire with water spray.

## 6. Accidental release measures

**Personal precautions**

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

**Environmental precautions**

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

**Methods for cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

## 7. Handling and storage

**Handling**

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

**Safe handling advice**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Comply with the health and safety at work laws. If material is a coating, do not sand, flame cut, braze or weld dry coating without an appropriate respirator or appropriate ventilation, and gloves.

**Advice on protection against fire and explosion**

Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

**Storage**

**Requirements for storage areas and containers**

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. The storage and use of this product is subject to the requirements of the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). Up to 50 litres of such highly flammable liquids may be stored in a work area provided they are kept in a fire-proof cupboard or bin. Larger quantities must be kept in a separate storeroom conforming to the structural requirements of the regulations. Further guidance is contained in the HSE ACOP L135, "Storage of Dangerous Substances."

**Advice on common storage**

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

Copies may be made only for those using Techpol Ltd products.

## 8. Exposure controls/personal protection

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

**Additional technical information on the plant**

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL,



Company Registration No: 4597527

VAT Registration No: 797 8388 38

**SAFETY DATA SHEET**

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

suitable respiratory protection must be worn. Mask with gas filter, type A (EN 141)

**National occupational exposure limits**

CAS-No.	Chemical Name	Source Time	Type	Value	Note
1330-20-7	xylene		STEL	441 mg/m <sup>3</sup>	
			STEL	100 ppm	
			TWA	220 mg/m <sup>3</sup>	
			TWA	50 ppm	
123-86-4	n-butyl acetate		STEL	966 mg/cm <sup>3</sup>	
			STEL	200 ppm	
			TWA	724 mg/cm <sup>3</sup>	
			TWA	150 ppm	
112-07-2	2-butoxyethyl acetate		STEL	50 ppm	
			TWA	20 ppm	
100-41-4	ethylbenzene		STEL	552 mg/m <sup>3</sup>	
			STEL	125 ppm	
			TWA	441 mg/m <sup>3</sup>	
			TWA	100 ppm	
85-44-9	phthalic anhydride		STEL	12 mg/m <sup>3</sup>	
			TWA	4 mg/m <sup>3</sup>	

**Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Hand protection**

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical Name	Glove material	Glove thickness	Break through time
xylene	Nitrile rubber	0.33 mm	30 min
	Viton (R) <sub>R</sub>	0.7 mm	480 min
n-butyl acetate	Viton (R) <sub>R</sub>	0.7 mm	10 min
	Nitrile rubber	0.33 mm	30 min
solvent naphtha (petroleum), light aroma. Viton (R) <sub>R</sub>		0.7 mm	30 min
(<0,1% benzene)			

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatrill <sub>R</sub> glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

**Eye protection**

Wear protective eyewear for protection against solvent spatter.

**Skin and body protection**

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fibre or of high temperature resistant synthetic fibre.

**Hygiene measures**

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

**Environmental exposure controls**

Do not let product enter drains. For ecological information refer to section 12.

**9. Physical and chemical properties****Appearance**

Company Registration No: 4597527

VAT Registration No: 797 8388 38

**SAFETY DATA SHEET**

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

Form: liquid      Colour: clear      Odour: Characteristic Paint Odour

**Important health, safety and environmental information**

	Value	Method
Flash point	24 _C	
Ignition temperature	370 _C	DIN 51794
Boiling point/boiling range	125 _C	
Lower explosion limit	0.5 %	
Upper explosion limit	12.3 %	
Vapour pressure	3.7 hPa	
Relative density	1.02 g/cm <sup>3</sup>	DIN 53217/ISO 2811
Water solubility	partly miscible	
Viscosity (23 _C)	<20 s	ISO 2431-1993 6 mm
Solvent separation test < 3% ADR/RID		
Content of volatile components (including water)	43.5%	Basis Vapour pressure >= 0.01 kPa
pH	Not applicable.	

**10. Stability and reactivity****Stability**

Stable

**Conditions to avoid**

Stable under recommended storage and handling conditions (see section 7).

**Materials to avoid**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**Hazardous decomposition products**

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

**11. Toxicological information****General observations**

There is no data available on the product. The product is classified and labelled in accordance with EC directives or respective national laws. See sections 3 and 15 for details.

**Practical experience**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorption, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Contains phthalic anhydride, neodecanoic acid, 2,3-epoxypropyl ester. May produce an allergic reaction.

Toxicity Test Type	Value	Time	Species
xylene			
Oral LD50	4,300 mg/kg		rat
Dermal LD50	> 1,700 mg/kg		rabbit
Inhalation LC50	5,000 ppm 4 h		rat
n-butyl acetate			
Oral LD50	> 5,000 ml/kg		rat
Dermal LD50	> 5,000 ml/kg		rabbit
Inhalation LC50	> 6,335 ppm 4 h		rat
2-butoxyethyl acetate			
Oral LD50	2,400 mg/kg		rat
Dermal LD50	1,500 mg/kg		rabbit
ethylbenzene			
Oral LD50	3,500 mg/kg		rat
Dermal LD50	17.8 g/kg		rabbit
Inhalation LC50	4,000 ppm 4 h		rat
solvent naphtha (petroleum), light aroma. (<0,1% benzene)			
Oral LD50	> 5,000 mg/kg		rat
Dermal LD50	> 3,160 mg/kg		rat



Company Registration No: 4597527

VAT Registration No: 797 8388 38

## SAFETY DATA SHEET

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

Inhalation LD50	> 3,670 ppm 4 h		rat
1,2,4-trimethylbenzene			
Oral LD50	5,000 mg/kg	rat	
Inhalation LC50	18,000 mg/m3 4 h		rat
phthalic anhydride			
Oral LD50	1,530 mg/kg	rat	
Dermal LD50	> 10 g/kg		rabbit
Inhalation LC50	> 210 mg/m3 1 h		rat
mesitylene			
Oral LD50	24,000 mg/kg	rat	
Inhalation LC50	24 mg/l 4 h		rat
neodecanoic acid, 2,3-epoxypropyl ester			
Oral LD50	> 10 mg/kg	rat	
Dermal LD50	> 4 mg/kg	rat	
Inhalation LC50	> 0.25 mg/l 4 h		rat
n-propylbenzene			
Oral LD50	6,040 mg/kg	rat	
Inhalation LD50	> 9,999 ppm 2 h		rat

## 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. The data in this section is consistent with data from chemical safety reports available at the date of revision. Product does not contain organic linked halogens contributing to AOX.

### Acute toxicity aquatic invertebrates

EINECS-No.	Chemical Name	Species	Type	Exposure time	Value	Method
265-199-0	solvent naphtha (petroleum), light aroma. (<0,1% benzene)	Daphnia	EC50	24 h	170 mg/l	
202-436-9	1,2,4-trimethylbenzene	Daphnia	LC50	48 h	6 mg/l	
203-604-4	mesitylene	Daphnia	EC50	48 h	6 mg/l	
247-979-2	neodecanoic acid, 2,3-epoxypropyl Ester	Daphnia	EC50	48 h	5 ml/g	
203-132-9	n-propylbenzene	Daphnia	EC50	24 h	2 mg/l	

### Acute and extended toxicity of fishes

EINECS-No.	Chemical Name	Species	Type	Exposure time	Value	Method
265-199-0	solvent naphtha (petroleum), light aroma. (<0,1% benzene)	Brachydanio rerio (zebra fish)	LC50	96 h	10 mg/l	
202-436-9	1,2,4-trimethylbenzene	Oncorhynchus mykiss (rainbow trout)	EC50	96 h	9.22 mg/l	
203-604-4	mesitylene	Carassius auratus (goldfish)	LC50	96 h	12.5 mg/l	
247-979-2	neodecanoic acid, 2,3-epoxypropyl Ester	Oncorhynchus mykiss (rainbow trout)	LC50	96 h	5 mg/l	

### Toxicity with aquatic plants

EINECS-No.	Chemical Name	Species	Type	Exposure time	Value	Method
265-199-0	solvent naphtha (petroleum), light aroma. (<0,1% benzene)	Algae	EC50	72 h	10 mg/l	

### Mobility

No information available.

### Persistence and degradability

No information available

### Bio accumulative potential

No information available.

### Other adverse effects

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 3 and 15 for details.



Company Registration No: 4597527

VAT Registration No: 797 8388 38

## SAFETY DATA SHEET

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

### 13. Disposal considerations

Dispose of in accordance with local regulations.

#### Product:

Recommendation:

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

Waste Key Number	Description
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances

#### Uncleaned packaging:

Recommendation:

Properly emptied containers are to be scrap processed or reconditioned. Improperly emptied containers are considered hazardous waste (waste key number 150110). Waste, including emptied containers, is controlled waste. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. If fully drained containers are compacted they can be regarded as Controlled Waste and disposed of in accordance with the requirements of the Control of Pollution Act 1974 and the Environmental Protection Act 1990 (GB), the Pollution Control and Local Government (NI) Order 1978 (NI) or of the EC (Waste) Regulations 1979 and the EC (Toxic & Dangerous Waste) Regulations 1982 (IRL).

### 14. Transport information

Transport only in accordance with the requirements of the Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labeling), ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

#### ADR/RID (Land transport)

Proper shipping name:	PAINT
UN-Number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III
Tunnel restriction code:	D/E
Special Provision:	640E
Hazchem:	3Y

#### IMDG (Sea transport)

Proper shipping name:	PAINT
UN-Number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III
Marine Pollutant:	N
EmS:	F-E,S-E

#### ICAO/IATA (Air transport)

Proper shipping name:	PAINT
UN-Number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III

### 15. Regulatory information

The product is labelled according to the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 as amended (CHIP Regulations). The risk associated with the use of this product must be assessed in accordance with the Control of Substances Hazardous to Health (COSHH) Regulations and the Dangerous Substances and Explosive Atmospheres Regulations.

#### Symbol and indication of hazard.

Xn	Harmful
	Contains xylene.

#### R-phrases(s)

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Company Registration No: 4597527

VAT Registration No: 797 8388 38

## SAFETY DATA SHEET

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

### S-phrases(s)

S23	Do not breathe vapour/spray.
S36/37	Wear suitable protective clothing and gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.

Contains epoxy constituents. See information supplied by the manufacturer. Contains: phthalic anhydride; neodecanoic acid, 2,3-epoxypropyl ester. May produce an allergic reaction.

### National legislation

This safety datasheet has been prepared according to British legislation.

The product is labelled according to the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 as amended (CHIP Regulations). The risk associated with the use of this product must be assessed in accordance with the Control of Substances Hazardous to Health (COSHH) Regulations and the Dangerous Substances and Explosive Atmospheres Regulations.

## 16. Other information

Full text of R phrases with no. appearing in section 3

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R42/43	May cause sensitization by inhalation and skin contact.
R43	May cause sensitization by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

### Information taken from reference works and the literature.

Substance No. CAS no: [www.cas.org/EQ/regsys.html](http://www.cas.org/EQ/regsys.html)  
EC no: <http://ecb.jrc.it/esis/index.php?PGM=ein>

Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC. <http://ecb.jrc.it/existing-chemicals/>  
<http://ecb.jrc.it/classification-labelling/>  
<http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB>  
<http://www.cdc.gov/niosh/ipcs/icstart.html>

Other directives, limitations and prohibitory Regulations  
Directive 76/769/EC  
Directive 98/24/EC  
Directive 90/394/EC  
Directive 79/393/EC  
Directive 1999/45/EC  
Directive 2006/8/EC  
EUR-LEX: <http://europa.eu.int/eur-lex/lex>

Exposure limit for the pure substance <http://osha.europa.eu/OSHA>

### Training advice

Directive 76/769/EC  
Directive 98/24/EC

### Further information



Company Registration No: 4597527

VAT Registration No: 797 8388 38



## SAFETY DATA SHEET

according to 1907/2006/EC 10747 v9.0 Revision Date: 2019/01/01

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

### Report version

Version	Changes
9.	0 4

Revision Date: 2019/01/01

### Annex - Exposure scenarios

An exposure scenario is a description of use conditions which allows the risk of a substance or mixture to humans or the environment to be controlled. The exposure scenario is based on the initial scenarios of the chemicals used in this preparation. Up to the time of issuing this SDS there were no initial exposure scenarios available. The product is only for industrial and/or professional use, not for any consumer use.

Company Registration No: 4597527



VAT Registration No: 797 8388 38