

# SAFETY DATA SHEET according to regulation 1907/2006

**silco**<sup>®</sup>**Product name: 1818-C-0,4****Creation date: 08.10.2010, Revision: 19.04.2022, version: 1.2**

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product name

1818-C-0,4

UFI:

NY00-6032-P00G-436U

<https://my.chemius.net/p/XqQsbk/en/pd/en>

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Paint.

Uses advised against

No information.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Šentrupert 5 a

3303 Gomilsko, Slovenia

+386 3 703 3180

msds@silco.si

### 1.4 Emergency Telephone Number

Emergency

112

Manufacturer

+386 3 703 3180

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229.1 Pressurised container: May burst if heated.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: Danger**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight  $\leq 700$ ).  
May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with national regulation.

**Contains:**

acetone

n-butyl acetate

**Special provisions**

Without adequate ventilation, explosive vapors may accumulate. Without adequate ventilation, explosive vapors may accumulate.

**2.3 Other hazards**

No information.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substances**

For mixtures see 3.2.

**3.2 Mixtures**

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
acetone	67-64-1 200-662-2 606-001-00-8	25-50	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	/	/
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	10-<20	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	/	/
butane	106-97-8 203-448-7 601-004-00-0	10-<20	Flam. Gas 1; H220 Press. Gas; H280	/	C

propane	74-98-6 200-827-9 601-003-00-5	10-<20	Flam. Gas 1; H220 Press. Gas; H280	/	U
xylene	1330-20-7 215-535-7 601-022-00-9	5-<10	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 STOT RE 2; H373	/	C
isobutane	75-28-5 200-857-2 601-004-00-0	5-<10	Flam. Gas 1; H220 Press. Gas; H280	/	C, U
titanium dioxide	13463-67-7 236-675-5 022-006-00-2	5-<10	Carc. 2; H351	/	10, V, W
reaction product: bisphenol-A- (epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 603-074-00-8	0,1-<1	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	Skin Irrit. 2; H315; C ≥ 5% Eye Irrit. 2; H319; C ≥ 5%	/

### Notes for substances

10	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.
C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.  In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
V	If the substance is to be placed on the market as fibres (with diameter < 3> 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
W	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

## SECTION 4: FIRST AID MEASURES

### 4.1 First aid measures

#### General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

#### Following inhalation

Remove patient to fresh air - move out of dangerous area. Victim should rest in a warm place. If difficulties with breathing do not stop, search for medical help. If victim is not breathing give artificial respiration. Seek medical help

immediately.

**Following skin contact**

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. Wash contaminated clothes and shoes before reuse. If symptoms develop and persist, seek medical attention.

**Following eye contact**

Immediately flush eyes with running water, keeping eyelids apart. If irritation does not stop, seek professional medical treatment!

**Following ingestion**

Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

**4.2 Most important symptoms and effects, both acute and delayed****Following inhalation**

Vapours may cause drowsiness and dizziness. Intoxication, vertigo, headache, nausea.

**Following skin contact**

May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

**Following eye contact**

Redness, tearing, pain.

**Following ingestion**

Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area. May cause nausea/vomiting and diarrhea. May cause abdominal discomfort.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information.

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media****Suitable extinguishing media**

Foam.  
Fire extinguishing powder.  
Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

Full water jet.

**5.2 Special hazards arising from the substance or mixture****Hazardous combustion products**

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

**5.3 Advice for firefighters****Protective actions**

In case of fire or heating do not breathe fumes/vapours. Cool the endangered containers with water spray. Vapours can form explosive mixtures with air.

**Special protective equipment for fire-fighters**

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

**Additional information**

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

**Protective equipment**

Use personal protective equipment (Section 8).

**Precautionary measures**

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

**Emergency procedures**

Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Do not breathe vapour or mist. Avoid contact with skin and eyes.

For emergency responders

Use personal protective equipment.

### 6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

For containment

No information.

For cleaning up

Make sure the leakage site is well aired. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

**OTHER INFORMATION**

See Section 7: safe handling.

### 6.4 Reference to other sections

See also sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

**Protective measures**

**Measures to prevent fire**

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material. Vapours and air form explosive mixtures.

**Measures to prevent aerosol and dust generation**

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

**Measures to protect the environment**

No information.

**Other measures**

No information.

**Advice on general occupational hygiene**

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist. Remove contaminated clothes and wash them before reuse. Consider measures required in Section 8 of this safety data sheet.

## 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Store in accordance with local regulations. Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs.

### Packaging materials

The original container of producer.

### Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking.

### Storage class

No information.

### Further information on storage conditions

No information.

## 7.3 Specific end use(s)

### Recommendations

No information.

### Industrial sector specific solutions

No information.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Occupational Exposure limit values

Name	mg/m <sup>3</sup>	ml/m <sup>3</sup>	Short-term value mg/m <sup>3</sup>	Short-term value ml/m <sup>3</sup>	Remark	Biological Tolerance Values
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
Butane (106-97-8)	1450	600	1810	750	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	/
Acetone (67-64-1)	1210	500	3620	1500	/	/
Butyl acetate (123-86-4)	724	150	966	200	/	/
Titanium dioxide respirable (13463-67-7)	4	/	/	/	/	/
Titanium dioxide total inhalable (13463-67-7)	10	/	/	/	/	/

#### Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

#### DNEL/DMEL values

##### For product

No information.

##### For components

No information.

#### PNEC values

##### For product

No information.

##### For components

No information.

## 8.2 Exposure controls

### Appropriate engineering control

#### Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Do not eat, drink or smoke while working.

#### Structural measures to prevent exposure

No information.

#### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

### Personal protective equipment

#### Eye and face protection

Tight fitting protective goggles (EN 166).

#### Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately.

### Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber	≥ 0.7 mm	≥ 60 min	/

### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345). Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). Choose body protection according to the activity and possible exposure.

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. In case of insufficient ventilation wear mask with filter AX (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

### Thermal hazards

No information.

### Environmental exposure controls

#### Substance/mixture related measures to prevent exposure

No information.

#### Instruction measures to prevent exposure

No information.

#### Organisational measures to prevent exposure

No information.

#### Technical measures to prevent exposure

No information.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

#### Physical state

liquid - aerosol

#### Colour

white

#### Odour

characteristic solvent like

#### Important health, safety and environmental information

Odour threshold	No information.
-----------------	-----------------

pH	substance/mixture is non-polar/aprotic
Melting point/Freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	No information.
Evaporation rate	No information.
Flammability (solid, gas)	> 200 °C
Explosion limits (vol%)	No information.
Vapour pressure	No information.
Vapour density	No information.
Density / weight	Density: 0.78872 g/cm <sup>3</sup> at 20 °C
Solubility	Water: Insoluble
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Oxidising properties	No information.

## 9.2 OTHER INFORMATION

Weight organic solvents	83.6 % 654 g/l (VOC) 645 g/l (VOC (RFU))
-------------------------	--

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

### 10.3 Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions. Vapours and air can form flammable or explosive mixtures.

### 10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks. Do not store above 50°C.

### 10.5 Incompatible materials

Oxidants.

### 10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### (a) Acute toxicity

##### For product

Exposure route	Type	Species	Time	value	Method	Remark
dermal	ATE	/	/	12553 mg/kg	/	/
inhalation	ATE	/	/	> 54.9 mg/l	/	/

##### For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
acetone	oral	LD <sub>50</sub>	rat	/	5800 mg/kg	/	/
acetone	dermal	LD <sub>50</sub>	rabbit	/	20000 mg/kg	/	/
acetone	inhalation	LC <sub>50</sub>	rat	4 h	ca. 76 mg/l	/	/
n-butyl acetate	oral	LD <sub>50</sub>	rat	/	13100 mg/kg	/	/
n-butyl acetate	dermal	LD <sub>50</sub>	rabbit	/	> 5000 mg/kg	/	/
n-butyl acetate	inhalation	LC <sub>50</sub>	rat	4 h	> 21 mg/l	/	/
butane	inhalation	LC <sub>50</sub>	rat	4 h	658 mg/l	/	/
propane	inhalation	LC <sub>50</sub>	rat	4 h	20 mg/l	/	/
xylene	oral	LD <sub>50</sub>	rat	/	3523 mg/kg	/	/
xylene	dermal	LD <sub>50</sub>	/	/	1100 mg/kg	/	/
xylene	inhalation	LC <sub>50</sub>	/	4 h	11 mg/l	/	/
isobutane	inhalation	LC <sub>50</sub>	rat	4 h	658 mg/l	/	/
titanium dioxide	oral	LD <sub>50</sub>	rat	/	> 20000 mg/kg	/	/
titanium dioxide	dermal	LD <sub>50</sub>	rabbit	/	> 10000 mg/kg	/	/
titanium dioxide	inhalation	LC <sub>50</sub>	rat	4 h	> 6.82 mg/l	/	/

#### (b) Skin corrosion/irritation

No information.

##### Additional information

The product is not classified as irritating to the skin.

#### (c) Serious eye damage/irritation

No information.

##### Additional information

Causes serious eye irritation.

#### (d) Respiratory or skin sensitisation

No information.

##### Additional information

It contains at least one ingredient that can cause sensitisation. Can cause allergic reaction.

#### (e) (Germ cell) mutagenicity

No information.

#### (f) Carcinogenicity

No information.

#### (g) Reproductive toxicity

No information.

##### Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

#### (h) STOT-single exposure

No information.

##### Additional information

May cause drowsiness or dizziness.

(i) STOT-repeated exposure

No information.

Additional information

STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

No information.

Additional information

Aspiration hazard: Not classified.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

Acute (short-term) toxicity

No information.

Chronic (long-term) toxicity

No information.

### 12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

No information.

### 12.3 Bioaccumulative potential

Partition coefficient

No information.

Bioconcentration factor (BCF)

No information.

### 12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

### 12.5 Results of PBT and vPvB assessment

No evaluation.

### 12.6 Other adverse effects

No information.

### 12.7 Additional information

For product

Water hazard class 2 (self-assessment): hazardous for water. Do not allow to reach ground water, water courses or

sewage system. Danger for drinking water if even small quantities leak into ground water.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

#### Product / Packaging disposal

##### Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems. Do not dispose together with household garbage.

##### Waste codes / waste designations according to LoW

16 05 04\* - gases in pressure containers (including halons) containing dangerous substances

##### Packaging

Deliver completely emptied containers to approved waste disposal authorities.

##### Waste codes / waste designations according to LoW

15 01 04 - metallic packaging

##### Waste treatment-relevant information

No information.

##### Sewage disposal-relevant information

No information.

##### Other disposal recommendations

No information.

## SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2 UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class(es)			
2	2	2	2
			
14.4 Packing group			
Not given/not applicable	Not given/not applicable	Not given/not applicable	Not given/not applicable
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			

Limited quantities 1 L Special provisions 190, 327, 344, 625 Packing Instructions P207, LP200 Special packing provisions PP87, RR6, L2 Transport category 2 Tunnel restriction code (D)	Limited quantities 1 L EmS F-D, S-U	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y203 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 30 kg G Packing Instructions (Pkg Inst) 203 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 kg Special provisions A145, A167, A802	Limited quantities 1 L
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>			
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)  
EU limit values and category: B(e) 840 g/l. VOC Content: 654 g/l

Regulation EC 648/2004 on detergents  
No information.

Special instructions  
Seveso III, P3a: flammable aerosols.

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION

Indication of changes  
No information.

Key literature references and sources for data  
No information.

### Abbreviations and acronyms

ATE - Acute Toxicity Estimate  
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
CEN - European Committee for Standardisation  
C&L - Classification and Labelling  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CAS# - Chemical Abstracts Service number  
CMR - Carcinogen, Mutagen, or Reproductive Toxicant  
CSA - Chemical Safety Assessment  
CSR - Chemical Safety Report  
DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level  
DPD - Dangerous Preparations Directive 1999/45/EC  
DSD - Dangerous Substances Directive 67/548/EEC  
DU - Downstream User  
EC - European Community  
ECHA - European Chemicals Agency  
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)  
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)  
EEC - European Economic Community  
EINECS - European Inventory of Existing Commercial Substances  
ELINCS - European List of notified Chemical Substances  
EN - European Standard  
EQS - Environmental Quality Standard  
EU - European Union  
Euphrac - European Phrase Catalogue  
EWC - European Waste Catalogue (replaced by LoW – see below)  
GES - Generic Exposure Scenario  
GHS - Globally Harmonized System  
IATA - International Air Transport Association  
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG - International Maritime Dangerous Goods  
IMSBC - International Maritime Solid Bulk Cargoes  
IT - Information Technology  
IUCLID - International Uniform Chemical Information Database  
IUPAC - International Union for Pure Applied Chemistry  
JRC - Joint Research Centre  
Kow - octanol-water partition coefficient  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)  
LE - Legal Entity  
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
LR - Lead Registrant  
M/I - Manufacturer / Importer  
MS - Member States  
MSDS - Material Safety Data Sheet  
OC - Operational Conditions  
OECD - Organization for Economic Co-operation and Development  
OEL - Occupational Exposure Limit  
OJ - Official Journal  
OR - Only Representative  
OSHA - European Agency for Safety and Health at work  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEC - Predicted Effect Concentration  
PNEC(s) - Predicted No Effect Concentration(s)  
PPE - Personal Protection Equipment  
(Q)SAR - Qualitative Structure Activity Relationship  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RIP - REACH Implementation Project  
RMM - Risk Management Measure  
SCBA - Self-Contained Breathing Apparatus  
SDS - Safety data sheet  
SIEF - Substance Information Exchange Forum  
SME - Small and Medium sized Enterprises  
STOT - Specific Target Organ Toxicity  
(STOT) RE - Repeated Exposure  
(STOT) SE - Single Exposure  
SVHC - Substances of Very High Concern  
UN - United Nations  
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.