

SAFETY DATA SHEET according to regulation 1907/2006

silco®**Product name: 6090-1****Creation date: 30.01.2020, Revision: 19.04.2022, version: 1.4**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name

6090-1

UFI:

2VUH-Y0Y9-K00V-9AM1

<https://my.chemius.net/p/GwMIV9/en/pd/en>

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Putty.

Uses advised against

No information.

1.3 Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Šentrupert 5 a

3303 Gomilsko, Slovenia

+386 3 703 3180

msds@silco.si

1.4 Emergency Telephone Number

Emergency

112

Manufacturer

+386 3 703 3180

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

Repr. 2; H361d Suspected of damaging the unborn child.

STOT RE 1; H372 Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: Danger**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

P101 IF medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Contains:

styrene

2.3 Other hazards

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

For mixtures see 3.2.

3.2 Mixtures

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	10- \leq 20	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 Repr. 2; H361 STOT RE 1; H372 Aquatic Chronic 3; H412	/	/

SECTION 4: FIRST AID MEASURES**4.1 First aid measures****General notes**

Symptoms of poisoning may even occur after several hours; therefore medical observation is required at least 48 hours

after the event. Person giving first aid should properly protect himself. If breathing is difficult or if not breathing provide artificial respiration. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. Take off all contaminated clothing immediately. When it is suspected, that there may still be harmful vapours/fumes present in the air, respiratory protection (mask; self contained breathing apparatus) must be used.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms occur, seek medical advice. If victim is not breathing give artificial respiration. In case of unconsciousness bring patient into stable side position and seek medical attention. In the event of breathing difficulties, get medical advice/attention immediately.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention. If irritation of skin persists seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. After initial flushing, remove any contact lenses and continue flushing. Seek medical help.

Following ingestion

Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

Following skin contact

Itching, redness, pain.

Following eye contact

Redness, tearing, pain.

Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort.

4.3 Indication of any immediate medical attention and special treatment needed

No information.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂).

Fire extinguishing powder.

Water spray. Fight larger fires with water spray.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of heating harmful vapours/gases can be generated.

5.3 Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated extinguishing agents must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel****Protective equipment**

Use personal protective equipment (Section 8). Avoid contact with the eyes and skin. Do not breathe vapours/smoke!

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Keep away sources of ignition.

Emergency procedures

Evacuate the danger zone. Prevent access to unprotected personnel. Prevent access to unauthorised personnel.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up**For containment**

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Do not use water or water based cleansing agents. Dispose in accordance with applicable regulations (see Section 13).

OTHER INFORMATION

See Section 7: safe handling.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling****Protective measures****Measures to prevent fire**

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges. Ensure proper grounding of the equipment. Vapours and air form explosive mixtures. Use spark-proof tools.

Measures to prevent aerosol and dust generation

Ensure good ventilation and extraction. Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin and eyes.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Store in accordance with local regulations. Keep in cool and well ventilated area. Keep in tightly closed container. Protect from open fire, heat and direct sunlight. Keep away from sources of ignition - no smoking. Keep away from oxidising substances. Store below 30°C. Keep away from food, drink and animal feeding stuffs. Keep unauthorized personnel away.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Do not store in unlabelled containers. Close opened containers after use. Put the containers upright to prevent from leaking. The floor of the storage room must be impermeable and dam spilled liquid.

Storage class

No information.

Further information on storage conditions

Storage class: storage must comply with the regulations on storage of flammable chemicals.

7.3 Specific end use(s)**Recommendations**

No information.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Occupational Exposure limit values**

Name	mg/m ³	ml/m ³	Short-term value mg/m ³	Short-term value ml/m ³	Remark	Biological Tolerance Values
Styrene (100-42-5)	430	100	1080	250	/	/

Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values**For product**

No information.

For components

Name	Type	Exposure route	exp. frequency	Remark	value
styrene	Worker	inhalation	long term systemic effects	/	85 mg/m ³
styrene	Worker	inhalation	short term systemic effects	/	289 mg/m ³
styrene	Worker	inhalation	short term local effects	/	306 mg/m ³
styrene	Worker	dermal	long term systemic effects	/	406 mg/kg bw/day
styrene	Consumer	inhalation	long term systemic effects	/	10.2 mg/m ³

styrene	Consumer	inhalation	short term systemic effects	/	174.25 mg/m ³
styrene	Consumer	inhalation	short term local effects	/	182.75 mg/m ³
styrene	Consumer	dermal	long term systemic effects	/	343 mg/kg bw/day
styrene	Consumer	oral	long term systemic effects	/	2.1 mg/kg bw/day

PNEC values

For product

No information.

For components

Name	Exposure route	Remark	value
styrene	fresh water	/	0.028 mg/L
styrene	marine water	/	0.014 mg/L
styrene	fresh water sediment	dry weight	0.614 mg/kg
styrene	marine water sediment	dry weight	0.307 mg/kg
styrene	soil	dry weight	0.2 mg/kg
styrene	water treatment plant	/	5 mg/L
styrene	water, intermittent release	fresh water	0.4 mg/L

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with eyes and skin. Do not breathe vapours/aerosols.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Store protective clothing separate from regular clothing.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Before use protect hands with suitable protective cream. Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed. Unsuitable gloves: Natural rubber, Chloroprene rubber, Nitrile rubber, Butyl rubber, PVC gloves.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Viton (fluorinated rubber)	≥ 0.7 mm	≥ 480 min	EN 374-4

Skin protection

Wear suitable protective clothing. Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

Thermal hazards

No information.

Environmental exposure controls**Substance/mixture related measures to prevent exposure**

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

No information.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties****Physical state**

liquid - paste

Colour

different colours colourless

Odour

characteristic

Important health, safety and environmental information

Odour threshold	No information.
pH	substance/mixture is non-soluble (in water)
Melting point/Freezing point	No information.
Initial boiling point/boiling range	145 °C
Flash point	31 °C
Evaporation rate	No information.
Flammability (solid, gas)	480 °C
Explosion limits (vol%)	1.2 – 8.9 vol %
Vapour pressure	6 hPa at 20 °C
Vapour density	No information.
Density / weight	Density: 1.2 – 1.9 g/cm ³ at 20 °C
Solubility	Water: Insoluble
Partition coefficient	No information.
Auto-ignition temperature	(Not self-igniting.)
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Oxidising properties	No information.

9.2 OTHER INFORMATION

Weight organic solvents	120 g/l (VOC) 120 g/l (VOC (RFU))
-------------------------	--------------------------------------

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under recommended transport or storage conditions.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

Risk of exothermic polymerization.

10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5 Incompatible materials

Peroxide. Free radicals. Exothermic polymerisation

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Decomposition products may include toxic gas.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects****(a) Acute toxicity**

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
styrene	oral	LD ₅₀	rat	/	5000 mg/kg	/	/
styrene	dermal	LD ₅₀	rat	/	> 2000 mg/kg	OECD 402	/
styrene	inhalation	LC ₅₀	rat	4 h	11.8 mg/l	/	/

Additional information

The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

No information.

Additional information

Causes skin irritation.

(c) Serious eye damage/irritation

No information.

Additional information

Causes serious eye irritation.

(d) Respiratory or skin sensitisation

No information.

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

For components

Name	Exposure route	Type	Species	Time	value	result	Method	Remark
styrene	inhalation (vapours)	NOAEL	rat	/	4.34 mg/l	/	OECD 453	5 days per week, 6 h per day

(g) Reproductive toxicity

For components

Name	Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
styrene	Effects on fertility	NOAEL (parents)	rat	/	0.65 - 2.2 mg/L	/	OECD 416	Inhalation (vapour)
styrene	Effects on fertility	NOAEL (F2)	rat	/	0.22 mg/L	/	OECD 416	Inhalation (vapour)
styrene	Developmental toxicity	NOAEL	rat	/	2.6 mg/L	/	/	Inhalation
styrene	Teratogenicity	NOAEL	rat	/	2.6 mg/L	/	/	Inhalation
styrene	Maternal toxicity	LOAEL	rat	/	1.3 mg/L	/	/	Inhalation

Summary of evaluation of the CMR properties

Suspected of damaging the unborn child.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

For components

Name	Exposure route	Type	Species	Time	Exposure	organ	value	result	Method	Remark
styrene	inhalation (vapours)	NOAEL	rat	13 weeks	sub-acute	/	0.85 mg/L	/	/	6h/day
styrene	inhalation (vapours)	NOAEL	rat	/	sub-chronic	/	mg/L	/	OECD 453	6h/day

Additional information

Causes damage to the hearing organs through prolonged or repeated exposure if inhaled.

(j) Aspiration hazard

No information.

Additional information

Aspiration hazard: Not classified.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
styrene	LC ₅₀	4.02 mg/L	96 h	fish	<i>Pimephales promelas</i>	/	/
styrene	EC ₅₀	4.7 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	/
styrene	EC ₅₀	4.9 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050 EPA OTS 797.1050	/
styrene	EC ₅₀	ca. 500 mg/L	30 min	bacteria	/	OECD 209 OECD 209	/
styrene	EC ₁₀	0.28 mg/L	96 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050 EPA OTS 797.1050	/

Chronic (long-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
styrene	NOEC	1.01 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	/

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

Name	Type	Rate	Time	Evaluation	Method	Remark
styrene	biodegradability	70.9 %	28 days	readily biodegradable	ISO DIN 9408	aerobic, activated sludge

12.3 Bioaccumulative potential

Partition coefficient

For components

Name	Media	value	Temperature °C	pH	Concentration	Method
styrene	Octanol-water (log Pow)	2.96	/	/	/	/

Bioconcentration factor (BCF)

For components

Name	Species	organism	value	Duration	Evaluation	Method	Remark
styrene	BCF	fish	13.5	/	/	/	/
styrene	BCF	/	74	/	/	/	Calculated value

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

For components

Name	Type	Criterion	value	Evaluation	Method	Remark
styrene	Soil	log KOC	2.55	/	/	/
styrene	Soil	/	352	/	/	Koc

12.5 Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6 Other adverse effects

No information.

12.7 Additional information

For product

Do not allow to reach ground water, water courses or sewage system. Danger for drinking water if even small quantities leak into ground water. Water hazard class 2 (self-assessment): hazardous for water.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Do not dispose together with household garbage. Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

07 02 08* - other still bottoms and reaction residues

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Dispose of in accordance with applicable waste disposal regulation.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

Disposal in accordance with the Rules on the management of waste.





Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number			
UN 1866	UN 1866	UN 1866	UN 1866
14.2 UN proper shipping name			
RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION
14.3 Transport hazard class(es)			
3	3	3	3
			
14.4 Packing group			
III	III	III	III
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			

Limited quantities 5 L Packing Instructions P001, IBC03, LP01, R001 Special packing provisions PP1 Transport category 3 Tunnel restriction code (D/E)	Limited quantities 5 L EmS F-E, S-E Flash point 31 °C	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y344 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 10 L Packing Instructions (Pkg Inst) 355 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 L Special provisions A3	Limited quantities 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code			
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(b) 250 g/l. VOC Content: < 120 g/l

Regulation EC 648/2004 on detergents

No information.

Special instructions

Seveso P5c: FLAMMABLE LIQUIDS. Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes

No information.

Key literature references and sources for data

No information.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
 ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 CEN - European Committee for Standardisation
 C&L - Classification and Labelling
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 CAS# - Chemical Abstracts Service number
 CMR - Carcinogen, Mutagen, or Reproductive Toxicant
 CSA - Chemical Safety Assessment
 CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.