

SAFETY DATA SHEET according to regulation 1907/2006



Product name: 9230 Hardener

Creation date: 24.08.2022, **Revision:** 24.08.2022, **version:** 2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name
9230 Hardener

Product code
[9230]



<https://my.chemius.net/p/slwl7/en/pd/en>

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses
No information.

Uses advised against
No information.

1.3 Details of the supplier of the safety data sheet

Supplier
SILCO d.o.o.
Sentrupert 5a
3303 Gomilsko, Slovenia
+386 3 703 3180
msds@silco.si

1.4 Emergency Telephone Number

Emergency
112

Supplier
112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.
Skin Sens. 1; H317 May cause an allergic skin reaction.
STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: Warning**

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

P240 Ground and bond container and receiving equipment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulation.

2.3 Other hazards

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

For mixtures see 3.2.

3.2 Mixtures

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	40-70	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	/	/
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 -	25-50	Skin Sens. 1; H317 EUH204	/	/
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	5-15	Flam. Liq. 3; H226	/	/
xylene	1330-20-7 215-535-7 601-022-00-9	0-10	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332	/	/

SECTION 4: FIRST AID MEASURES**4.1 First aid measures****General notes**

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Obtain professional medical help!

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Consult a physician. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed**Following inhalation**

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Vapours may cause drowsiness and dizziness.

Following skin contact

Contact with skin may cause irritation (redness, itching). May cause sensitisation by skin contact (itching, redness, rashes). Repeated exposure may cause dry skin or cracked skin.

Following eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media****Suitable extinguishing media**

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture**Hazardous combustion products**

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3 Advice for firefighters**Protective actions**

In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training. Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air. Reacts with water (moisture) release of carbon dioxide and pressure build-up may cause closed container to burst. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

No information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

No information.

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

Emergency procedures

No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use only explosion-proof instruments and equipment. Use spark-proof tools. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises. Do not rinse contaminated area with water or aqueous cleansing agents. Ensure ventilation of the containers in which waste is stored as CO₂ can be formed. Clean contaminated area with plenty of water.

OTHER INFORMATION

No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep in a cool, dry and well ventilated place. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances. Keep away from sources of ignition - no smoking. Keep away from moisture and water.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions

No information.

7.3 Specific end use(s)

Recommendations

No information.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

Name	mg/m ³	ml/m ³	Short-term value mg/m ³	Short-term value ml/m ³	Remark	Biological Tolerance Values
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift 650 mmol methyl hippuric acid/mol creatinine in urine - Post shift 650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
1-Methoxypropyl acetate (108-65-6)	274	50	548	100	Sk	/
Butyl acetate (123-86-4)	724	150	966	200	/	/

Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values

For product

No information.

For components

Name	Type	Exposure route	exp. frequency	Remark	value
n-butyl acetate	Worker	inhalation	long term systemic effects	/	300 mg/m ³
n-butyl acetate	Worker	inhalation	short term systemic effects	/	600 mg/m ³

n-butyl acetate	Worker	inhalation	long term local effects	/	300 mg/m ³
n-butyl acetate	Worker	inhalation	short term local effects	/	600 mg/m ³
n-butyl acetate	Worker	dermal	long term systemic effects	/	11 mg/kg bw/day
n-butyl acetate	Worker	dermal	short term systemic effects	/	11 mg/kg bw/day
n-butyl acetate	Consumer	inhalation	long term systemic effects	/	35.7 mg/m ³
n-butyl acetate	Consumer	inhalation	short term systemic effects	/	300 mg/m ³
n-butyl acetate	Consumer	inhalation	long term local effects	/	35.7 mg/m ³
n-butyl acetate	Consumer	inhalation	short term local effects	/	300 mg/m ³
n-butyl acetate	Consumer	dermal	long term systemic effects	/	6 mg/kg bw/day
n-butyl acetate	Consumer	dermal	short term systemic effects	/	6 mg/kg bw/day
n-butyl acetate	Consumer	oral	long term systemic effects	/	2 mg/kg bw/day
n-butyl acetate	Consumer	oral	short term systemic effects	/	2 mg/kg bw/day
Hexamethylene diisocyanate, oligomers	Worker	inhalation	long term local effects	/	0.5 mg/m ³
Hexamethylene diisocyanate, oligomers	Worker	inhalation	short term local effects	/	1 mg/m ³
2-methoxy-1-methylethyl acetate	Worker	inhalation	long term systemic effects	/	275 mg/m ³
2-methoxy-1-methylethyl acetate	Worker	inhalation	short term local effects	/	550 mg/m ³
2-methoxy-1-methylethyl acetate	Worker	dermal	long term systemic effects	/	796 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Consumer	inhalation	long term systemic effects	/	33 mg/m ³
2-methoxy-1-methylethyl acetate	Consumer	inhalation	long term local effects	/	33 mg/m ³
2-methoxy-1-methylethyl acetate	Consumer	dermal	long term systemic effects	/	320 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Consumer	oral	long term systemic effects	/	36 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Consumer	oral	short term systemic effects	/	500 mg/kg bw/day
xylene	Worker	inhalation	long term systemic effects	/	221 mg/m ³
xylene	Worker	inhalation	short term systemic effects	/	442 mg/m ³
xylene	Worker	inhalation	long term local effects	/	221 mg/m ³
xylene	Worker	inhalation	short term local effects	/	442 mg/m ³
xylene	Worker	dermal	long term systemic effects	/	212 mg/kg bw/day
xylene	Consumer	inhalation	long term systemic effects	/	65.3 mg/m ³
xylene	Consumer	inhalation	short term systemic effects	/	260 mg/m ³
xylene	Consumer	inhalation	long term local effects	/	65.3 mg/m ³
xylene	Consumer	inhalation	short term local effects	/	260 mg/m ³
xylene	Consumer	dermal	long term systemic effects	/	125 mg/kg bw/day
xylene	Consumer	oral	long term systemic effects	/	12.5 mg/kg bw/day

PNEC values

For product

No information.

For components

Name	Exposure route	Remark	value
n-butyl acetate	fresh water	/	0.18 mg/L
n-butyl acetate	water, intermittent release	/	0.36 mg/L
n-butyl acetate	marine water	/	0.018 mg/L
n-butyl acetate	water treatment plant	/	35.6 mg/L
n-butyl acetate	fresh water sediment	dry weight	0.981 mg/kg
n-butyl acetate	marine water sediment	dry weight	0.098 mg/kg
n-butyl acetate	soil	dry weight	0.09 mg/kg
Hexamethylene diisocyanate, oligomers	fresh water	/	0.127 mg/L
Hexamethylene diisocyanate, oligomers	water, intermittent release	/	1.27 mg/L
Hexamethylene diisocyanate, oligomers	marine water	/	0.013 mg/L
Hexamethylene diisocyanate, oligomers	water treatment plant	/	88 mg/L
Hexamethylene diisocyanate, oligomers	fresh water sediment	dry weight	266701 mg/kg
Hexamethylene diisocyanate, oligomers	marine water sediment	dry weight	26670 mg/kg
Hexamethylene diisocyanate, oligomers	soil	dry weight	53183 mg/kg
2-methoxy-1-methylethyl acetate	fresh water	/	0.635 mg/L
2-methoxy-1-methylethyl acetate	water, intermittent release	/	6.35 mg/L
2-methoxy-1-methylethyl acetate	marine water	/	0.064 mg/L
2-methoxy-1-methylethyl acetate	water treatment plant	/	100 mg/L
2-methoxy-1-methylethyl acetate	fresh water sediment	dry weight	3.29 mg/kg
2-methoxy-1-methylethyl acetate	marine water sediment	dry weight	0.329 mg/kg
2-methoxy-1-methylethyl acetate	soil	dry weight	0.29 mg/kg
xylene	fresh water	/	0.327 mg/L
xylene	water, intermittent release	/	0.327 mg/L
xylene	marine water	/	0.327 mg/L
xylene	water treatment plant	/	6.58 mg/L
xylene	fresh water sediment	dry weight	12.46 mg/kg
xylene	marine water sediment	dry weight	12.46 mg/kg
xylene	soil	dry weight	2.31 mg/kg

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Skin protection

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). At high risk of skin exposure chemical suits (EN ISO 6530:2005) and boots may be required (EN ISO 20345:2012).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid

Colour

No information.

Odour

No information.

Important health, safety and environmental information

Odour threshold	No information.
pH	No information.
Melting point/Freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	No information.
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	No information.
Vapour pressure	No information.
Vapour density	No information.
Density / weight	No information.
Solubility	No information.
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.

Explosive properties	No information.
Oxidising properties	No information.

9.2 OTHER INFORMATION

No information.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Reacts with water: may cause overpressure in closed vessel (CO₂).

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures.

10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5 Incompatible materials

Oxidants.

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

(a) Acute toxicity

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
n-butyl acetate	dermal	LD ₅₀	rabbit	/	5000 mg/kg	/	/
n-butyl acetate	inhalation	LC ₅₀	rat	4 h	9.6 - 29.2 mg/l	/	dust/aerosol
n-butyl acetate	oral	LD ₅₀	rat	/	4700 mg/kg	/	/
Hexamethylene diisocyanate, oligomers	oral	LD ₅₀	rat	/	> 5000 mg/kg	/	/
Hexamethylene diisocyanate, oligomers	dermal	LD ₅₀	rabbit	/	> 2000 mg/kg	/	/

Hexamethylene diisocyanate, oligomers	inhalation	LC ₀	rat	4 h	2.18 mg/l	/	/
2-methoxy-1-methylethyl acetate	oral	LD ₅₀	rat	/	8530 mg/kg	/	/
2-methoxy-1-methylethyl acetate	inhalation	LC ₅₀	rat	4 h	35.7 mg/l	/	vapour
2-methoxy-1-methylethyl acetate	dermal	LD ₅₀	rat	/	5000 mg/kg	/	/
xylene	oral	LD ₅₀	rat	/	> 3523 mg/kg	/	/
xylene	dermal	LD ₅₀	rabbit	/	4200 mg/kg	/	/
xylene	inhalation (vapours)	LC ₅₀	rat	4 h	29 mg/l	/	/

Additional information

The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

No information.

Additional information

The product is not classified as irritating to skin and eyes.

(c) Serious eye damage/irritation**For components**

Name	Exposure route	Species	Time	result	Method	Remark
2-methoxy-1-methylethyl acetate	/	/	/	May cause irritation.	/	/

(d) Respiratory or skin sensitisation

No information.

Additional information

May cause an allergic skin reaction. The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

No information.

Additional information

May cause drowsiness or dizziness. STOT SE (single exposure): Not classified.

(i) STOT-repeated exposure

No information.

Additional information

Repeated exposure may cause skin dryness or cracking. STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

No information.

Additional information

Aspiration hazard: Not classified.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
n-butyl acetate	LC ₅₀	18 mg/L	96 h	fish	/	/	/
n-butyl acetate	EC ₅₀	44 mg/L	48 h	crustacea	/	/	/
n-butyl acetate	EC ₅₀	675 mg/L	72 h	algae	/	/	/
Hexamethylene diisocyanate, oligomers	EC ₅₀	100 mg/L	48 h	daphnia	/	/	/
Hexamethylene diisocyanate, oligomers	EC ₅₀	51 mg/L	72 h	algae	/	/	/
2-methoxy-1-methylethyl acetate	LC ₅₀	100 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	/	/
2-methoxy-1-methylethyl acetate	EC ₅₀	500 mg/L	48 h	crustacea	/	/	/
xylene	LC ₅₀	13.4 mg/L	96 h	fish	<i>Pimephales promelas</i>	/	/
xylene	LC ₅₀	13.1 - 16.5 mg/L	96 h	fish	<i>Lepomis macrochirus</i>	/	/
xylene	LC ₅₀	2661 - 4093 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	/	/
xylene	LC ₅₀	19 mg/L	96 h	fish	<i>Lepomis macrochirus</i>	/	/
xylene	LC ₅₀	30.26 - 40.75 mg/L	96 h	fish	<i>Poecilia reticulata</i>	/	/
xylene	LC ₅₀	23.53 - 29.97 mg/L	96 h	fish	<i>Pimephales promelas</i>	/	/
xylene	LC ₅₀	7711 - 9591 mg/L	96 h	fish	<i>Lepomis macrochirus</i>	/	/
xylene	LC ₅₀	780 mg/L	96 h	fish	<i>Cyprinus carpio</i>	/	/
xylene	LC ₅₀	> 780 mg/L	96 h	fish	<i>Cyprinus carpio</i>	/	/
xylene	LC ₅₀	13.5 - 17.3 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	/	/
xylene	EC ₅₀	3.82 mg/L	48 h	daphnia	/	/	/

Chronic (long-term) toxicity

No information.

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

No information.

12.3 Bioaccumulative potential

Partition coefficient

No information.

Bioconcentration factor (BCF)

For components

Name	Species	organism	value	Duration	Evaluation	Method	Remark
2-methoxy-1-methylethyl acetate	organism	/	0.43	/	/	/	/

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 Results of PBT and vPvB assessment

No evaluation.

12.6 Other adverse effects

No information.

12.7 Additional information

For product

Product is not classified as dangerous for environment. Do not allow to reach ground water, water courses or sewage system.

For components

2-methoxy-1-methylethyl acetate

Water hazard class 1 (Self-assessment): slightly hazardous for water

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

No information.

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

No information.





Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number			
UN 1263	UN 1263	UN 1263	UN 1263
14.2 UN proper shipping name			
PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)			
3	3	3	3
			
14.4 Packing group			
III	III	III	III
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			
Limited quantities 5 L Special provisions 163, 367, 650 Packing Instructions P001, IBC03, LP01, R001 Special packing provisions PP1 Transport category 3 Tunnel restriction code (D/E)	Limited quantities 5 L EmS F-E, <u>S-E</u>	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y344 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 10 L Packing Instructions (Pkg Inst) 355 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 L Cargo Aircraft Only, Packing Instructions (CAO, Pkg Inst) 366 Special provisions A3, A72, A192 ERG code 3L	Limited quantities 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code			
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)
not applicable

Regulation EC 648/2004 on detergents
No information.

Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION**Indication of changes**

1.2 Relevant identified uses of the substance or mixture and uses advised against 2.1 Classification of the substance or mixture 2.2 Label elements 4.1 First aid measures 4.2 Most important symptoms and effects, both acute and delayed 5.1 Extinguishing media 5.2 Special hazards arising from the substance or mixture 5.3 Advice for firefighters 6.1 Personal precautions, protective equipment and emergency procedures 6.3 Methods and material for containment and cleaning up 7.1 Precautions for safe handling 7.2 Conditions for safe storage, including any incompatibilities 8.1 Control parameters 8.2 Exposure controls 9.1 Information on basic physical and chemical properties 9.2 OTHER INFORMATION 11.1 Information on toxicological effects 12.1 Toxicity 12.2 Persistence and degradability 12.3 Bioaccumulative potential 12.4 Mobility in soil 13.1 Waste treatment methods 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Key literature references and sources for data

No information.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
 ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 CEN - European Committee for Standardisation
 C&L - Classification and Labelling
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 CAS# - Chemical Abstracts Service number
 CMR - Carcinogen, Mutagen, or Reproductive Toxicant
 CSA - Chemical Safety Assessment
 CSR - Chemical Safety Report
 DMEL - Derived Minimal Effect Level
 DNEL - Derived No Effect Level
 DPD - Dangerous Preparations Directive 1999/45/EC
 DSD - Dangerous Substances Directive 67/548/EEC
 DU - Downstream User
 EC - European Community
 ECHA - European Chemicals Agency
 EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
 EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
 EEC - European Economic Community
 EINECS - European Inventory of Existing Commercial Substances
 ELINCS - European List of notified Chemical Substances
 EN - European Standard
 EQS - Environmental Quality Standard
 EU - European Union
 Euphrac - European Phrase Catalogue
 EWC - European Waste Catalogue (replaced by LoW – see below)
 GES - Generic Exposure Scenario
 GHS - Globally Harmonized System
 IATA - International Air Transport Association
 ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
 IMDG - International Maritime Dangerous Goods
 IMSBC - International Maritime Solid Bulk Cargoes
 IT - Information Technology
 IUCLID - International Uniform Chemical Information Database
 IUPAC - International Union for Pure Applied Chemistry
 JRC - Joint Research Centre

Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.