



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** **4202 ACCELERO 2K VOC PRIMER GREY**
 - **Article number:** 4202
 - **UFI:** 4V74-U09P-X007-6776
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

use as industrial paint
No further relevant information available.
- **Sector of Use**

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**

PC9a Coatings and paints, thinners, paint removers
PC9b Fillers, putties, plasters, modelling clay
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
Générale de Peinture,
70 Rue Cortambert 75116 Paris, France
info@generalpaint.biz
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number:** +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
 - **Hazard pictograms**



GHS02

- **Signal word** Warning

(Contd. on page 2)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 1)

• Hazard statements

H226 Flammable liquid and vapour.

• Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• 2.3 Other hazards

• Results of PBT and vPvB assessment

• PBT: Not applicable.

• vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

• 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:

| | | |
|--|---|-----------|
| CAS: 7727-43-7 EINECS: 231-784-4 | barium sulphate, natural substance with a Community workplace exposure limit | >10-≤25% |
| CAS: 1332-58-7 | Kaolin substance with a Community workplace exposure limit | >2.5-≤10% |
| CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27 | Solvent naphtha (petroleum), light arom. ⚠ Acute Tox. 4, H332; STOT SE 3, H335 | >2.5-≤10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32 | xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | >2.5-≤10% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | >2.5-≤10% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56 | 2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 | >2.5-≤10% |

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 2)

CAS: 112-07-2
EINECS: 203-933-3
Reg.nr.: 01-2119475112-47

2-butoxyethyl acetate
⚠ Acute Tox. 4, H312; Acute Tox. 4, H332

≤2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
 - **General information:** Immediately remove any clothing soiled by the product.
 - **After inhalation:** Supply fresh air; consult doctor in case of complaints.
 - **After skin contact:** Immediately rinse with water.
 - **After eye contact:** Rinse opened eye for several minutes under running water.
 - **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:**7727-43-7 barium sulphate, natural**

| | |
|-----|---|
| WEL | Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust |
|-----|---|

1332-58-7 Kaolin

| | |
|-----|--------------------------------------|
| WEL | Long-term value: 2 mg/m ³ |
|-----|--------------------------------------|

1330-20-7 xylene

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
|-----|--|

123-86-4 n-butyl acetate

| | |
|-----|---|
| WEL | Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
|-----|---|

108-65-6 2-methoxy-1-methylethyl acetate

| | |
|-----|--|
| WEL | Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk |
|-----|--|

112-07-2 2-butoxyethyl acetate

| | |
|-----|---|
| WEL | Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk |
|-----|---|

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 4)

· Ingredients with biological limit values:**1330-20-7 xylene**

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

· Respiratory protection: Not required.**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

GB

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

| | |
|------------------|-----------------|
| Form: | Liquid |
| Colour: | Grey |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |

· pH-value: Not determined.

· Change in condition

| | |
|--|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 124 °C |

· Flash point: 25 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 370 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

| | |
|--------|-----------|
| Lower: | 1.1 Vol % |
| Upper: | 7 Vol % |

· Vapour pressure at 20 °C: 6.7 hPa

· Density at 20 °C: 1.64 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

| | |
|------------|-----------------|
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |

· Solvent content:

| | |
|-------------------|-----------|
| Organic solvents: | 28.2 % |
| VOC (EC) | 461.7 g/l |

Solids content: 75.3 %

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**64742-95-6 Solvent naphtha (petroleum), light arom.**

| | | |
|------------|----------|--------------------|
| Oral | LD50 | >6,800 mg/kg (rat) |
| Dermal | LD50 | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |

1330-20-7 xylene

| | | |
|--------|------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 7)


SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|----------------------|
| • 14.1 UN-Number | UN1263 |
| • ADR, IMDG, IATA | |
| • 14.2 UN proper shipping name | 1263 PAINT |
| • ADR | PAINT |
| • IMDG, IATA | |
| • 14.3 Transport hazard class(es) | |
| • ADR, IMDG, IATA | |
|  | |
| • Class | 3 Flammable liquids. |
| • Label | 3 |

(Contd. on page 9)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 8)

| | |
|--|--|
| · 14.4 Packing group | III |
| · ADR, IMDG, IATA | |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
- None of the ingredients is listed.

(Contd. on page 10)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2021

Revision: 20.08.2020

Trade name: 4202 ACCELERO 2K VOC PRIMER GREY

(Contd. of page 9)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

- **Department issuing SDS:** Product safety department

- **Contact:** N/A

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - inhalation – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB