

# S7100

## MATTING ADDITIVE



### DESCRIPTION

S7100 Matting Additive can be used in S5000 HS Top Clear.

### SYROX REFINISH SYSTEM



### PRODUCT LIST

- S7100 MATTING ADDITIVE
- S5000 HS TOP CLEAR
- S6000 HS ACTIVATOR SLOW
- S6010 HS ACTIVATOR STANDARD
- S6020 HS ACTIVATOR FAST

### FEATURES

- For repairing matt and semi-matt finishes.
- For use on underhood and add on parts only.
- Can be used in SYROX S5000 HS TOP CLEAR.



TECHNICAL DATA SHEET

S7100


MATTING ADDITIVE




Product preparation - application STANDARD



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Surfaces have to be prepared according to the recommendations in the TDS of the selected quality.



Clear	Activator	Volume	
S5000	S6000 / S6010 / S6020	3	1

Mixing recommendation for:  
- S5000 HS TOP CLEAR

All mixing weights are: Clear / Additive

MATT  
Weight (g): 270 / 730

SEMI-MATT  
By weight (g): 330 / 670

SATIN GLOSS  
By weight (g): 380 / 620

All Syrox Activators except S6030



Refer to the original TDS of the selected quality.



For drying options, see details page.

VOC compliant

2004/42/IIB(e)(840) 600: The EU limit value for this product (product category: IIB(e)) in ready to use form is maximum 840 g/l of VOC. The VOC content of this product in ready to use form is maximum 600 g/l.

# TECHNICAL DATA SHEET

## S7100

## MATTING ADDITIVE



### Products

S7100 MATTING ADDITIVE


S5000 HS TOP CLEAR

S6000 HS ACTIVATOR SLOW

S6010 HS ACTIVATOR STANDARD

S6020 HS ACTIVATOR FAST


### Product mix



Mixing ratios with special agents are available in the productmix table on Colour Search and in the specific TDS.



\* 15 min bake required  
\* 15 min bake required  
Refer to the original TDS of the selected quality.



S7100 MATTING ADDITIVE can be overcoated with itself within 24 hours, with scuff sanding



Clean after use with a suitable solventbased guncleaner.

### Remarks

- Material has to be at room temperature (18-25°C) before use.
- Degree of flatness is depending on application. A wet coat gives higher gloss than a light coat.
- Thorough stirring of S7100 Matting Additive is required before mixing with S5000. Ensure all components are well stirred when making ready for use.
- The use of different activators, methods of application, drying conditions and film thicknesses leads to different gloss levels (up to 20%).
- S7100 Matting Additive will extend normal drying times.
- S7100 MATTING ADDITIVE / S5000 HS TOP CLEAR mixture to be applied over Syrox Basecoat or sanded well prepared and cleaned existing finishes.
- Refer to the original TDS of the selected system.

# TECHNICAL DATA SHEET

**S7100**

**MATTING ADDITIVE**



Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our Syrox product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our Syrox product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.